



DESIGNATOR	ANSI SIZE	D	M	S
FNX06a	1/4-20 [M6x1]	4/16 [6]	13/64 [5.2]	25/64 [10.0]
FNX08a	5/16-18 [M8x1.25]	5/16 [8]	17/64 [6.8]	32/64 [13.0]
FNX10a	3/8-16 [M10x1.5]	6/16 [10]	21/64 [8.4]	40/64 [16.0]
FNX12a	7/16-14 [M12x1.75]	8/16 [12]	27/64 [10.8]	45/64 [18.0]
FNX14a	1/2-13 [M14x2]	9/16 [14]	32/64 [12.8]	53/64 [21.0]
FNX16a	5/8-11 [M16x2]	10/16 [16]	37/64 [14.8]	60/64 [24.0]
FNX20a	3/4-10 [M20x2.5]	12/16 [20]	45/64 [18.0]	112/64 [30.0]
FNX24a	1-8 [M24x3]	15/16 [24]	54/64 [21.5]	126/64 [36.0]
FNX30a	1 1/4-7 [M30x3.5]	1 3/16 [30]	1 1/64 [25.6]	1 52/64 [46.0]
FNX36a	1 3/8-6 [M36x4]	1 7/16 [36]	1 14/64 [31.0]	2 2/64 [55.0]

CLASS 5 HEX NUTS

FNX06a-36a

SHEET NO.

DATE:

1 OF 2

2006

SPECIFICATIONS

Zinc-coated nuts shall be manufactured according to the dimensions and tolerances included in ANSI B18.2.4.1M for Style 1 hex nuts (shown in drawing). Corrosion resistant nuts shall be manufactured according to the dimensions and tolerances in ANSI B18.2.4.6M for heavy hex nuts (not shown in drawing). Nuts shall conform to the requirements of AASHTO M291M (ASTM A563M) for Class 5 nuts. Corrosion resistant nuts shall have geometric properties defined in ANSI B18.2.4.1M but shall have mechanical and material properties conforming to AASHTO M291M (ASTM A563M) for Class 8S3 nuts. Threads shall conform to ANSI B1.13M Class 6H. Zinc-coated nuts shall be treated according to either AASHTO M232 (ASTM A153) for Class C or AASHTO M298 (ASTM B695) for Class 50, Type 1.

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

INTENDED USE

These nuts are used in various sign support systems.

CLASS 5 HEX NUTS

FNX06a-36a

SHEET NO.

DATE

2 of 2