



DESIGNATOR	ANSI SIZE	D	M	S
FNX06c	$\frac{1}{4}$ -20 [M6x1]	$\frac{4}{16}$ [6]	$1\frac{3}{64}$ [5.2]	$2\frac{5}{64}$ [10.0]
FNX08c	$\frac{5}{16}$ -18 [M8x1.25]	$\frac{5}{16}$ [8]	$1\frac{7}{64}$ [6.8]	$3\frac{2}{64}$ [13.0]
FNX10c	$\frac{3}{8}$ -16 [M10x1.5]	$\frac{6}{16}$ [10]	$2\frac{1}{64}$ [8.4]	$4\frac{0}{64}$ [16.0]
FNX12c	$\frac{7}{16}$ -14 [M12x1.75]	$\frac{8}{16}$ [12]	$2\frac{7}{64}$ [10.8]	$4\frac{5}{64}$ [18.0]
FNX14c	$\frac{1}{2}$ -13 [M14x2]	$\frac{9}{16}$ [14]	$3\frac{2}{64}$ [12.8]	$5\frac{3}{64}$ [21.0]
FNX16c	$\frac{5}{8}$ -11 [M16x2]	$1\frac{0}{16}$ [16]	$3\frac{7}{64}$ [14.8]	$6\frac{0}{64}$ [24.0]
FNX20c	$\frac{3}{4}$ -10 [M20x2.5]	$1\frac{2}{16}$ [20]	$4\frac{5}{64}$ [18.0]	$11\frac{2}{64}$ [30.0]
FNX24c	1-8 [M24x3]	$1\frac{5}{16}$ [24]	$5\frac{4}{64}$ [21.5]	$12\frac{6}{64}$ [36.0]
FNX30c	$1\frac{1}{4}$ -7 [M30x3.5]	$1\frac{3}{16}$ [30]	$1\frac{1}{64}$ [25.6]	$15\frac{2}{64}$ [46.0]
FNX36c	$1\frac{3}{8}$ -6 [M36x4]	$1\frac{7}{16}$ [36]	$11\frac{4}{64}$ [31.0]	$2\frac{2}{64}$ [55.0]

CLASS 10 HEX NUTS

FNX06c-36c

SHEET NO.

DATE:

1 OF 2

2006

INTENDED USE

Zinc-coated nuts shall be manufactured according to the dimensions and tolerances included in ANSI B18.2.4.1M for Style 1 hex nuts (shown in drawing). Nuts shall conform to the requirements of AASHTO M291M (ASTM A563M) for Class 10 nuts. Threads shall conform to ANSI B1.13M Class 6H. Zinc-mated nuts shall be treated according to either AASHTO M232 (ASTM A153) Class C or AASHTO M298 (ASTM B695) Class 50, Type 1.

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

INTENDED USE

These nuts are used in various sign support systems.

CLASS 10 HEX NUTS

FNX06c-36c

SHEET NO.

DATE

2 of 2