



DESIGNATOR	L	W	D
PDE20	72 [1829]	6 [152]	8 [203]

WHITE PINE GUARDRAIL POST



PDE20

SHEET NO.

DATE:

1 of 2

8/14/2012

SPECIFICATIONS

Posts shall be made of white pine timber with a stress grade of at least 1200 psi [8 MPa]. Timber grading shall be in accordance with AASHTO M168. Timber for posts shall be either rough sawn (unplaned) or S4S (surfaced four sides) with dimensions indicated. The size tolerance of posts in the direction parallel to the axis of the bolt holes shall not be more than $\pm 1/4"$ [6 mm]. Only one type of surface finish shall be used for posts and blockouts in any one continuous length of guardrail.

All timber shall receive a preservation treatment in accordance with AASHTO M133 after all end cuts are made and all holes are drilled.

Inertial properties shown below are based on the nominal dimensions shown.

DESIGNATOR	AREA in. ² [10 ³ mm ²]	I _x in. ⁴ [10 ⁶ mm ⁴]	I _y in. ⁴ [10 ⁶ mm ⁴]	S _x in. ³ [10 ³ mm ³]	S _y in. ³ [10 ³ mm ³]
PDE20	48 [31.0]	256 [106.6]	144 [59.9]	64 [1049]	48 [786.6]

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

INTENDED USE

The white pine guardrail post is to be used in a variety of strong-post W-beam and thrie-beam systems including SGR20c.

CONTACT INFORMATION

Midwest Roadside Safety Facility
Nebraska Transportation Center
University of Nebraska-Lincoln
130 Whittier Research Center
2200 Vine Street
Lincoln, NE 68583-0965
(402) 472-0965
Email: mwrsf@unl.edu
Website: <http://mwrsf.unl.edu>

WHITE PINE GUARDRAIL POST

PDE20



SHEET NO.

DATE:

2 of 2

8/14/2012