



THRIE-BEAM BULLNOSE NOSE CABLE



RCM02

SHEET NO.

DATE:

1 of 2

4/17/2013

SPECIFICATIONS

The thrie-beam bullnose nose cable shall be “Cold Tuff” Button, S-409 Size No. 12, SB 2 7/8” [73], Stock No. 1040395 for 5/8” [16] D (6x25) wire rope (or any similarly sized swage-grip button ferrules).

The wire rope shall be 5/8” [16] diameter 6x19 wire strand core or independent wire rope core (IWRC), zinc-coated, right regular lay wire rope conforming to AASHTO M30.

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

INTENDED USE

The thrie-beam bullnose nose cable is intended for use in SET03a-b.

CONTACT INFORMATION

Midwest Roadside Safety Facility
Nebraska Transportation Center
University of Nebraska-Lincoln
130 Whittier Research Center
2200 Vine Street
Lincoln, NE 68583-0853
(402) 472-0965
Email: mwrfsf@unl.edu
Website: <http://mwrfsf.unl.edu>

THRIE-BEAM BULLNOSE NOSE CABLE

RCM02

SHEET NO.

DATE:

2 of 2

4/17/2013

