

INTENDED USE

Visi-BarrierTM is a highly visible, pre-cast polymer concrete traffic barrier, as well as a strong stayin-place form. The continuous visi-stripe on each panel is made from highly retro-reflective glass beads, which solve poor roadway delineation problems, especially on rainy nights when visibility is low. **Visi-Barrier's** polymer concrete provides high compressive and impact strength, a bright white surface, and superior resistance to salts, chlorides, and corrosion.

Visi-BarrierTM is available in standard, as well as modified shapes with various heights and panel lengths to suit specific needs. Designation SGM15c is 32"[813mm] high, standard NJ-Shape (New Jersey Safety-Shape) used for single or double-sided applications, and is accepted as an NCHRP Report 350 Test Level 4 (TL-4) barrier.

PHYSICAL PROPERTIES*

Property	Value	Test Method
Average Compressive Strength	14,000 psi [96 MPa]	ASTM C109
Average Flexural Strength	3200 psi [22 MPa]	ASTM C384
Splitting Tensile Strength	1600 psi [11 MPa]	ASTM D570
Impact Strength	100 ft-lbs [135 N-m]	ASTM D2444
Water Absorption	0.12 - 0.20%	ASTM D570
Fire Resistance	Class "A"	
Flame Spread	<25	ASTM E84
Smoke Development	<75	ASTM E84

*to be used for general guidelines only.

APPROVALS

Federal Highway Administration (FHWA) Acceptance Letter B-64, January 16, 1997. FHWA Letter from Richard D. Powers to Michael S. Stenko, March 7, 2005.

CONTACT INFORMATION

Transpo Industries, Inc. 20 Jones Street, New Rochelle, NY 10801 Phone: (914) 636-1000 Fax: (914) 636-1282 Email: info@transpo.com Web: www.transpo.com

VISI-BARRIER, NJ-SHAPE, 32" HIGH MEDIAN BARRIER

SGM15c

SHEET NO.	DATE
2 of 2	9/6/2013





The Smart Solutions Company