



| DESIGNATOR | BASE METAL<br>THICKNESS |  |
|------------|-------------------------|--|
| RWE01a     | 12 Gage [2.67]          |  |
| RWE01b     | 10 Gage [3.43]          |  |

# W-BEAM END SECTION (FLARED)



| ſ   | $\neg \cdot \cdot$ | I - I | $\sim$ 1 |        | 1  |
|-----|--------------------|-------|----------|--------|----|
| ł   | ٦١٨                | / F ( | ) [      | $\cap$ |    |
| - 1 | \ V \              | '   \ | ノー       | ()     | しし |

| SHEET NO. | DATE      |
|-----------|-----------|
| 1 of 2    | 3/18/2024 |

#### **SPECIFICATIONS**

W-Beam End Sections shall conform to the current requirements of AASHTO M180. RWE01a shall conform to AASHTO M180 Class A, and RWE01b shall conform to Class B.

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

### **INTENDED USE**

RWE01a-b End Sections are used in various W-Beam guardrail systems.

### **CONTACT INFORMATION**

Task Force 13 (TF13) a Non-Profit Association https://TF13.org

## W-BEAM END SECTION (FLARED)

| RWE01a-b  |           |  |  |
|-----------|-----------|--|--|
| SHEET NO. | DATE      |  |  |
| 2 of 2    | 3/18/2024 |  |  |

