



THE CROSS-SECTIONAL DIMENSIONS FOR THIS END ARE THE SAME AS PART RWB01a-b

THE CROSS-SECTIONAL DIMENSIONS FOR THIS END ARE THE SAME AS PART RTM01a

ELEVATION VIEW

Notes: (1) This transition section can be manufactured in right-hand or left-hand configurations.

### ASYMMETRICAL W-THRIE BEAM TRANSITION SECTION



**RWT02**

SHEET NO.

DATE:

1 of 2

5/17/2017

**SPECIFICATIONS**

Corrugated sheet steel beams shall conform to the current requirements of AASHTO M180. The asymmetrical W-Thrie beam transition section shall conform to AASHTO M180 Class B. Corrosion protection may be either Type II (zinc-coated) or Type IV (corrosion resistant steel). Corrosion resistant steel should conform to ASTM A606 for Type IV material and shall not be zinc-coated, painted or otherwise treated.

**INTENDED USE**

The transition section can be used to connect the SGR20a-b strong-post w-beam guardrail system to the SGR09a-c strong-post thrie beam guardrail.

**CONTACT INFORMATION**

Midwest Roadside Safety Facility  
Nebraska Transportation Center  
University of Nebraska-Lincoln  
130 Whittier Research Center  
2200 Vine Street  
Lincoln, NE 68583-0853  
(402) 472-0965  
Email: [mwrsf@unl.edu](mailto:mwrsf@unl.edu)  
Website: <http://mwrsf.unl.edu/>

**ASYMMETRICAL W-THRIE BEAM TRANSITION SECTION**



**RWT02**

SHEET NO.

DATE:

2 of 2

5/17/2017